

ASA BS-3000 ESD brushless electric screwdriver with AM-30 controller

Torque: 0.05 - 0.5 Nm

No load speed: 700 - 1000 rpm

Bit type: 1/4 HEX

Type: ESD type

Start type: lever start

Shut off: automatic

Direction: clockwise / counter-clockwise

Motor: brushless

Accuracy: +- 3%

Weight: 412 g

Length: 227 mm

Grip diameter: 33 mm

Machine screw size: 1 - 2.6 mm

Tapping screw size: 1 - 2.3 mm

Product informations AM-30 control unit: input voltage 100 - 240 VAC 50 / 60 Hz, output voltage 20 - 30 VDC, connection 5 pin, power 75 W, weight 450 g, dimension 172 x 81 x 61 mm

AM-30 electronic control unit setting: workpiece counter 1-60,000 pieces, 1-99 piece / work piece, screw time 0.01-9.99 seconds, parameter sets 10 pieces - sequence individually or sequentially adjustable from 0.01-9.99 seconds, Output signal / ready for operation - Torque reached - Workpiece complete OK - Single screw operation OK - Error screwdriving, input signal / release screwdriver
Scope of supply: ASA BS-3000 ESD screwdriver, AM-30 control unit, screwdriver cable

